



Powered by  
**ISUZU**



Generating

**80/100kVA**

**200/220V  
3-phase**

**400/440V  
3-phase**

Sound Level (no load@7m)

**61 dB(A)**

Dimension (mm)

**(L)2750-(W)1000-(H)1400**

Weight (kg)

**1800**

Engine (Diesel)

**Isuzu 6BG1**

**JPN T2**

Features

**Engine safety device**

**Large maintenance doors**

## Alternator

Rated Output	80/100kVA 64/ 80kW
Voltage-Three phase	200/220,400/440 V
Rated speed	1500/1800 rpm
Winding	Star with Neutral
Insulation class	H

## Engine

Type	Vertical Water-cooled 4-cycle Diesel
Model (Manufacturer)	DD-6BG1T(ISUZU)
Engine Emission	Japanese Tier2
Continuous rated output	73.1kW(99.4PS)/1500min <sup>-1</sup>
Rated speed,50/60Hz	1500/1800 rpm
Displacement	6.494L
Combustion system	Direct Injection, Turbo charger
Cooling method	Radiator, Water
Fuel tank capacity	219 L

## Features

Shutdowns	Lamp indication with shutdown
Warning	Lamp indication
Dimensions	2750*1000*1400mm, 1800kg
Sound Level (No Load)	61dB(A) @ 7m

Large maintenance side doors

Easy access to radiator & muffler

Removable side doors



Frequency Adjusting Screw

Emergency Stop Button

Indication lamp

Fuel Drain Plug

Coolant Drain Plug

External Fuel Intake

External Fuel Return



All doors are lockable

Fuel strainer